



# Oscillating Mountings

## AD-C



| Part no.   | Type           | G [N] |      | cd<br>[N/mm] | A   | B   | D                                | øE                                 | K       | □S | Weight<br>[kg] | Material structure                                                |
|------------|----------------|-------|------|--------------|-----|-----|----------------------------------|------------------------------------|---------|----|----------------|-------------------------------------------------------------------|
|            |                | K=2   | K=3  |              |     |     |                                  |                                    |         |    |                |                                                                   |
| 07 101 001 | <b>AD-C 18</b> | 150   | 120  | 23           | 100 | 50  | 55 <sup>0</sup> <sub>-0.3</sub>  | 13 <sup>0</sup> <sub>-0.2</sub>    | 40 × 20 | 18 | 0.8            | Steel welded construction,<br>aluminium profile,<br>painted blue. |
| 07 101 002 | <b>AD-C 27</b> | 300   | 240  | 31           | 120 | 60  | 65 <sup>0</sup> <sub>-0.3</sub>  | 16 <sup>+0.5</sup> <sub>-0.3</sub> | 55 × 34 | 27 | 1.6            |                                                                   |
| 07 101 003 | <b>AD-C 38</b> | 600   | 500  | 45           | 160 | 80  | 90 <sup>0</sup> <sub>-0.3</sub>  | 20 <sup>+0.5</sup> <sub>-0.2</sub> | 70 × 50 | 38 | 3.7            |                                                                   |
| 07 101 004 | <b>AD-C 45</b> | 1200  | 1000 | 50           | 200 | 100 | 110 <sup>0</sup> <sub>-0.3</sub> | 24 <sup>+0.5</sup> <sub>-0.2</sub> | 80 × 40 | 45 | 6.1            |                                                                   |

If no other units are specified, the numbers given are in mm.

G = max. load in N per element or rocker, by higher accelerations K, consult page 7.26.

cd = dynamic spring value by oscillation angles  $\alpha \pm 5^\circ$  in speed range of  $n_s = 300 - 600 \text{ min}^{-1}$

AD-C for center connection.