


# Rubber Suspension Element


## DO-A




sizes 15 to 45




sizes 15 to 45



size 50



size 50



2

| Part no.   | Type          | ø A                             | B       | D  | E    | F    | □S | G  | H  | L   | L1                               | Weight [kg] |
|------------|---------------|---------------------------------|---------|----|------|------|----|----|----|-----|----------------------------------|-------------|
| 01 041 001 | DO-A 15 × 25  | 5 <sup>+0.5</sup> <sub>0</sub>  | 10 ±0.2 | 28 | 25.5 | 53.5 | 15 | —  | —  | 25  | 30 <sup>0</sup> <sub>-0.3</sub>  | 0.07        |
| 01 041 002 | DO-A 15 × 40  | 5 <sup>+0.5</sup> <sub>0</sub>  | 10 ±0.2 | 28 | 25.5 | 53.5 | 15 | —  | —  | 40  | 45 <sup>0</sup> <sub>-0.3</sub>  | 0.11        |
| 01 041 003 | DO-A 15 × 60  | 5 <sup>+0.5</sup> <sub>0</sub>  | 10 ±0.2 | 28 | 25.5 | 53.5 | 15 | —  | —  | 60  | 65 <sup>0</sup> <sub>-0.3</sub>  | 0.15        |
| 01 041 004 | DO-A 18 × 30  | 6 <sup>+0.5</sup> <sub>0</sub>  | 12 ±0.3 | 34 | 31   | 65   | 18 | —  | —  | 30  | 35 <sup>0</sup> <sub>-0.3</sub>  | 0.12        |
| 01 041 005 | DO-A 18 × 50  | 6 <sup>+0.5</sup> <sub>0</sub>  | 12 ±0.3 | 34 | 31   | 65   | 18 | —  | —  | 50  | 55 <sup>0</sup> <sub>-0.3</sub>  | 0.20        |
| 01 041 006 | DO-A 18 × 80  | 6 <sup>+0.5</sup> <sub>0</sub>  | 12 ±0.3 | 34 | 31   | 65   | 18 | —  | —  | 80  | 85 <sup>0</sup> <sub>-0.3</sub>  | 0.31        |
| 01 041 007 | DO-A 27 × 40  | 8 <sup>+0.5</sup> <sub>0</sub>  | 20 ±0.4 | 47 | 44   | 91   | 27 | —  | —  | 40  | 45 <sup>0</sup> <sub>-0.3</sub>  | 0.32        |
| 01 041 008 | DO-A 27 × 60  | 8 <sup>+0.5</sup> <sub>0</sub>  | 20 ±0.4 | 47 | 44   | 91   | 27 | —  | —  | 60  | 65 <sup>0</sup> <sub>-0.3</sub>  | 0.47        |
| 01 041 009 | DO-A 27 × 100 | 8 <sup>+0.5</sup> <sub>0</sub>  | 20 ±0.4 | 47 | 44   | 91   | 27 | —  | —  | 100 | 105 <sup>0</sup> <sub>-0.3</sub> | 0.76        |
| 01 041 010 | DO-A 38 × 60  | 10 <sup>+0.5</sup> <sub>0</sub> | 25 ±0.4 | 63 | 60   | 123  | 38 | —  | —  | 60  | 70 <sup>0</sup> <sub>-0.3</sub>  | 0.88        |
| 01 041 011 | DO-A 38 × 80  | 10 <sup>+0.5</sup> <sub>0</sub> | 25 ±0.4 | 63 | 60   | 123  | 38 | —  | —  | 80  | 90 <sup>0</sup> <sub>-0.3</sub>  | 1.14        |
| 01 041 012 | DO-A 38 × 120 | 10 <sup>+0.5</sup> <sub>0</sub> | 25 ±0.4 | 63 | 60   | 123  | 38 | —  | —  | 120 | 130 <sup>0</sup> <sub>-0.3</sub> | 1.69        |
| 01 041 013 | DO-A 45 × 80  | 12 <sup>+0.5</sup> <sub>0</sub> | 35 ±0.5 | 85 | 73   | 150  | 45 | —  | —  | 80  | 90 <sup>0</sup> <sub>-0.3</sub>  | 1.84        |
| 01 041 014 | DO-A 45 × 100 | 12 <sup>+0.5</sup> <sub>0</sub> | 35 ±0.5 | 85 | 73   | 150  | 45 | —  | —  | 100 | 110 <sup>0</sup> <sub>-0.3</sub> | 2.27        |
| 01 041 015 | DO-A 45 × 150 | 12 <sup>+0.5</sup> <sub>0</sub> | 35 ±0.5 | 85 | 73   | 150  | 45 | —  | —  | 150 | 160 <sup>0</sup> <sub>-0.3</sub> | 3.37        |
| 01 041 026 | DO-A 50 × 120 | M12                             | 40 ±0.5 | 89 | 78   | 167  | 50 | 30 | 60 | 120 | 130 <sup>0</sup> <sub>-0.3</sub> | 3.30        |
| 01 041 029 | DO-A 50 × 160 | M12                             | 40 ±0.5 | 89 | 78   | 167  | 50 | 30 | 60 | 160 | 170 <sup>0</sup> <sub>-0.3</sub> | 4.40        |
| 01 041 027 | DO-A 50 × 200 | M12                             | 40 ±0.5 | 89 | 78   | 167  | 50 | 40 | 70 | 200 | 210 <sup>0</sup> <sub>-0.3</sub> | 5.50        |

List of torque and loads on page 2.3.

If no other units are specified, the numbers given are in mm.

Material structure: DO-A 50 available with nodular cast iron housings on request